

皮带驱动滚筒输送机 Belt driven roller conveyor

MODEL <BWBR-SERIES>

BWBR系列是非常适合的项目水平输送可用于储积、分岐、合流部分的输送工作。由线轴的传动方式安静、干净安全、皮带驱动，滚筒安装方便，输送能力强等优点。在物流流水线及分拣物流线中应用广泛。

The model "BWBR-SERIES" is ideally suited for horizontal conveying of items where transfers, side loading or unloading, or temporary accumulation is required.

● SPECIFICATIONS ●

- TREAD ROLLERS : $\Phi 50.8$, with a ball Bearing
- DRIVE BELT : Transmission belt (s -250)
- DRIVE DRUM : $\Phi 140 \times 100$ mm Rubber Coating
- TAIL DRUM : $\Phi 89.1 \times 100$ mm
- TAKE-UP DRUM : $\Phi 89.1 \times 100$ mm
- FRAME : 3.2T 180mm x 40mm NC , steel frame , with joint coupling
- LEG : 700mm~1,000mm(H)
- SPEED : 18,000mmPM
- BEARING : Precision , lubricated , ball bearing units with steel housing
- MOTOR DRIVE : 0.5HP, 2HP / 380V / 3PH / 50HZ/
Horizontal gear motor
- V-BELT & PULLEY : A Type
- BELT TAKE-UP : Screw type unit at take-up pulley
- CAPACITY : 300kg per 3000(mm)
- ELECTRICAL CONTROLS : available as option

● SPECIFICATIONS TABLE ●

Overall Width "A"	Between Frames Width "B" "A"-80	Roller Length "C"	Length "L"	Height "H"
510(mm)	430(mm)	Roller Length	3,000(mm)	500(mm)
610(mm)	530(mm)	=	6,000(mm)	~
~	~	Between	9,000(mm)	Adjustable
2,010(mm)	1,930(mm)	Frames	~	top of roller

- You can order a table which is not standard size.

