



↑ 物流标准设备认证书



↑ 爬坡皮带输送机安全认证书

爬坡皮带输送机 Incline belt conveyor

MODEL <BWIB-SERIES>

适用于室内及室外1F到2F的物品输送任务
经济实用，性价比高，模块化设计
条纹皮带，便于倾斜传送
多种附加装置可省人力等效。
对危险部位进行了内部处理，防止安全隐患

For moving cartons, cases, boxes, tote pans, etc. smoothly, and economically floor-to-floor, in either direction. Can be used as a booster in gravity flow systems.

● SPECIFICATIONS ●

- TREAD ROLLERS: $\Phi 50.8$, with a ball bearing
- BELT: Green Ruff-top belt
- DRIVE DRUM: $\Phi 190$ / Rubber Coating / Both Crown
- TAIL DRUM: $\Phi 140$ / Both Crown
- CENTER DRIVE: Reversible drive, Integral belt take-up (Model: TFU206)
- END DRIVE TAKE-UP: Integral belt take-up (Model: TFU205) at tail pulley
- FRAME: 125x40x20x3.2t, steel frame, with joint coupling
- BED: Box type, slide & roller / 750mm pitch
- SPEED: 25,000mm/PM
- BEARING: Precision, lubricated, ball bearing units with steel housing
- MOTOR DRIVE: 1HP, 2HP / 220V, 380V / 3HP / 50HZ, Horizontal gear motor
- CAPACITY: 25° Incline / Slide bed: * 1HP-170kg * 2HP-330kg
/ Roller bed: * 1HP-260kg * 2HP-520kg
- ELECTRICAL CONTROLS: available as option

● SPECIFICATIONS TABLE ●

Overall Width "A"	Between Frames Width "B" "A"-80	Belt Width "C" "A"-110	Length "L"	Height "H1, H2"
410(mm)	330(mm)	300(mm)	3,000(mm)	450(mm)
510(mm)	430(mm)	400(mm)	6,000(mm)	~
~	~	~	9,000(mm)	Adjustable
2,010(mm)	1,930(mm)	1,900(mm)	~	top of belt

- You can order a table which is not standard size.



这个角度是可以调节的
The angle can be adjusted.

