



↑ 倾斜皮带输送机 CE 认证



↑ 倾斜皮带输送机安全书

倾斜式皮带输送机 Portable belt conveyor

MODEL <BWPT-SERIES>

BWPT-系列产品可以用来传递从一端到另一端的物品输送. 皮带机的延伸部分可以伸展到卡车内部, 从而减少了对装卸输送的距离。

The longer Model 'BWPT-SERIES' can be used to convey material from one floor to another...or to a balcony area .Its long bed can also extend fad into a truck , thereby minimizing the distance for loading or unloading the conveyor.

● SPECIFICATIONS ●

- TREAD ROLLERS : $\Phi 50.8$, with a ball Bearing
- BELT : Green Ruff-top belt
- DRIVE DRUM : $\Phi 160$ / Rubber Coating /
Crown processing of surface
- TAIL DRUM : $\Phi 114$ / Crown processing of surface
- RETURN ROLLER : $\Phi 50.8$, with a ball bearing
- DRIVE DRUM (FEEDER) : $\Phi 114$ / crown processing of surface
- TAIL DRUM (FEEDER) : $\Phi 89.1$ / Crown processing of surface
- FRAME : 3.2T 135~237mm x 40mm , steel frame , with joint coupling
- BED : Box type , slide & roller / 500mm center
- INCLINE CONTROL : Manual (pumping) / Hydro Cylinder & unit
- SPEED : 25,000mmPM
- BEARING : Precision , lubricated , ball bearing units with
steel housing
- MOTOR DRIVE : 1HP / 220 , 380V / 3PH or 1PH / (1/30) geared
- CASTERS : $\Phi 150$ Urethane Casters
- CAPACITY : 25° Incline 200kg total distributed live load.
- FEEDER : Size 500BW x 1000L (Hinged bed)

● SPECIFICATIONS TABLE ●

Overall Width "A"	Between Frames Width "B" "A"-80	Belt Width "C" "A"-110	Length "L"	Height "H1"	Height "H2"
510(mm) ~	430(mm) ~	400(mm) ~	4,000(mm) or	600(mm) ~	1,100(mm) ~
1,010(mm)	930(mm)	900(mm)	5,000(mm)	730(mm)	2,200(mm)

- You can order a table which is not standard size.

